



FLOORHARD[®] CHEMSTRONG

High Performance Non Metallic Floor Hardener

PRODUCT DESCRIPTION:

FLOORHARD[®] CHEMSTRONG is a dry shake, non-metallic floor hardener with graded quartz sand aggregates in a high strength cementitious binder. The product is designed to provide a dense, tough surface capable of withstanding the abrasion and impact loading and specially suited for floors with frequent wetness. FLOORHARD[®] CHEMSTRONG is also available in 6 additional colours to the standard natural colour.

USES:

PRIMARY APPLICATIONS:

- Lobbies and waiting rooms of commercial and public buildings
- Corridors and washrooms in institutional and public buildings
- Restaurants and dairies
- Auto showrooms and service centres
- Factory and warehouse floors Maintenance Shops
- Car parking and driveways in commercial and industrial facilities
- Distribution Centres

FEATURES/BENEFITS:

- Provides a high strength wearing surfaces in areas subject to constant or frequently wet conditions.
- Use of hard and properly graded aggregates increases the wear resistance over plain concrete floors.
- Dense surface resists penetration of oil, grease and other liquids.
- Virtually dust-free floor
- Can be applied at the coverage rates up to 10 kg/m².

APPLICATION DATA:

DIRECTION FOR USE:

The contractor and engineer are encouraged to consult and review the Multichem bulletin 'Application Instruction-Dry Shake Floor Hardener'. The document offers instructions detailing the general installation of dry shake floor hardener.

Coloured dry shakes require special attention for uniform color.

Care should be taken with regards to the following:

1. Delay application of the shake as long as possible to get the maximum colour saturation at the surface of the slab.
2. Apply the shake as evenly as possible to get uniform colour.
3. Do not burnish trowel the floor. Best appearance is achieved by hand trowelling the final finish.

Curing and Sealing: The floor is recommended to be cured and sealed with **Concure R, FloorSeal Clear or Floorseal Color.**



MULTICHEM GROUP | 510, Exim Link MG Link Road, Nahur (W), Mumbai-400078,

Phone No.: 9619091025, 9323890195, e-mail: info@multichemgroup.net

www.multichemgroup.net

FLOORHARD[®] CHEMSTRONG /2013/R2-09122023



FLOORHARD® CHEMSTRONG

High Performance Non Metallic Floor Hardener

TECHNICAL DATA

Properties	Values
Coverage:	Approx. 2.5-10.0 kg/m ²
Relative Abrasion Resistance: (ASTM C779)	30-40% of Plain Cured Concrete (28 days)

STORAGE:

Store in dry, frost-free conditions at moderate temperatures not greater than 25 °c.

WARRANTY

Multichem warrants **FLOORHARD® CHEMSTRONG** to be free from manufacturing defects as defined in this warranty. Manufacturing defects are considered to be those defects that occur due to the quality of the ingredients or from the manufacturing process itself. This warranty does not include labor costs and other costs or expenses associated with the removal or installation of **FLOORHARD® CHEMSTRONG**.

Because the Multichem does not perform the actual installation, it cannot be held responsible for the results of the application. Multichem specifically disclaims problems that occur due to weather conditions, structural movement, structural design flaws and application techniques.

This warranty is in lieu of all other warranties expressed or implied including the warranty of merchantability and fitness of purpose and of all other obligations or liabilities on Multichem part. Multichem neither assumes nor authorizes any person to assume for Multichem any liability in connection with the sale and installation of **FLOORHARD® CHEMSTRONG**.

Because of constant improvement of manufacturing techniques and formulations, Company reserves rights to change this datasheet and its contents without prior notice.



MULTICHEM GROUP | 510, Exim Link MG Link Road, Nahur (W), Mumbai-400078,

Phone No.: 9619091025, 9323890195, e-mail: info@multichemgroup.net

www.multichemgroup.net

FLOORHARD® CHEMSTRONG /2013/R2-09122023