



MultiFix X TIMBERFIX

Ready mixed, highly flexible ceramic floor tile adhesive and grout suitable for direct application onto plywood, wooden floor boards and most composite boards

PRODUCT DESCRIPTION:

Multifix-TimerFix is a Ready mixed, highly flexible ceramic floor tile adhesive and grout suitable for direct application onto plywood, wooden floor boards and most composite boards.

TECHNICAL DATA:

Description	Results
Open Time	1 hour @ 25°C
Final Set	24 hours depending on Temperature and substrate
Colour	White Paste
Coverage	1.50 TO 3.00 kg per m ²
Packaging	25 kg bucket
Storage	Store above 5 °C and below 30 °C
Shelf Life	6 months in above conditions

APPLICATION DATA:

Ensure that the surface substrate being adhered to is clean, dry and firm. The surface should be free from dust, dirt, oil and grease or any other contaminants. Please ensure that the surface is strong enough to support the weight of the tile and adhesive. To encourage best adhesion to your substrate it is advisable when applying adhesive to porous surfaces that the area be primed. Super-Add-P/FlexiBond is an ideal surface primer, as it will help to prevent water penetration, increase bond strength.

Installation Methods:

Apply the adhesive to a thickness of 3 mm up to 1 m at a time. On internal walls use a notched trowel, leaving ribs i.e. 3mmX 3mm at 6mm centres for mosaics, 5mmX 5mm at 10 mm centres for wall tiles, use the solid bed trowel method.

Grouting:





MultiFix X TIMBERFIX

Ready mixed, highly flexible ceramic floor tile adhesive and grout suitable for direct application onto plywood, wooden floor boards and most composite boards

Leave for approximately 24 hours before grouting and/or walking on tiles (longer time may be required on impervious surfaces). Please consult our product guide for the recommended grout for application.

CLEANING:

All tools should be cleaned with water immediately after use.

STORAGE:

Store in dry, frost-free conditions at moderate temperature not greater than 25 °C.

SAFETY DATA:

-) **Irritating to eyes, respiratory systems and skin.**
-) **Risk of serious damage to eyes.**
-) **Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.**
-) **After contact with skin, wash immediately with plenty of clean water.**
-) **Wear suitable protective clothing, gloves and eye/face protection.**

Please consult our technical department for further information.

WARRANTY

Multichem warrants **MULTIFIX™** adhesives and grouts to be free from manufacturing defects as defined in this warranty. Manufacturing defects are considered to be those defects that occur due to the quality of the ingredients or from the manufacturing process itself. This warranty does not include labor costs and other costs or expenses associated with the removal or installation of **MULTIFIX™** adhesives and grouts.

Because the Multichem does not perform the actual installation, it cannot be held responsible for the results of the application. Multichem specifically disclaims problems that occur due to weather conditions, structural movement, structural design flaws and application techniques.

This warranty is in lieu of all other warranties expressed or implied including the warranty of merchantability and fitness of purpose and of all other obligations or liabilities on Multichem part. Multichem neither assumes nor authorizes any person to assume for Multichem any liability in connection with the sale and installation of **MULTIFIX™** adhesives and grouts.

Because of constant improvement of manufacturing techniques and formulations, Company reserves rights to change this datasheet and its contents without prior notice.



MULTICHEM GROUP | 510, Exim Link, MG Link Road, Nahur (W), Mumbai-400078, Phone No.: 91-22-25669137, 25664890, e-mail: info@multichemgroup.net
www.multichemgroup.net

MULTIFIX-TIMBERFIX/2016/R0-2016